



# ROCBIT GROUP

"Le Service"

## G - RH QL50 DTH Hammer

ITEM Discrimination	
Part List	
1	Top Sub
2	O Ring of Top Sub
3	Check Valve
4	Spring
5	Compression Buffer
6	Air Distributor
7	Internal Cylinder
8	Piston
9	Outer Cylinder
10	Guided Sleeve
11	Stop Ring
12	O Ring of Stop Ring
13	Drive Chuck

Length(Without Bit)	Weight	Outer Diameter	Bit Shanks	Rec. Bit hole
1024mm	69.00kg	Ø126mm	QL50	Ø140-Ø152mm
Working Pressure	Impact frequency	Recommend rotation	Air Consumption	Connection Thread
1.6-2.8Mpa	32HZ at 18bar	25-55r/min	1.8Mpa:17.0m <sup>3</sup> /min	2 3/8" API REG 3 1/2" API REG

ROCBIT DRILLING EQUIPMENT SA (PTY) LTD  
8 LAKE ROAD, DENLEE, GERMISTON, 1401

TEL: 011 824 0760

EMAIL: [salesadmin@rocbit.co.za](mailto:salesadmin@rocbit.co.za)

WEBSITE: [www.rocbit.co.za](http://www.rocbit.co.za)